

# Flex Type B PLL Lamp LT40W/8XX-ID

## Commercial Grade LED PLL/FT Lamp

### Descriptions:



The Flex (Type B) PLL lamps are designed to be the perfect retrofit solution to move from traditional fluorescent lamps to energy saving LEDs. This ballast bypass lamp has everything needed built into the lamp with proven energy savings, long life, surge suppression and industry leading safety features.


### Features & Benefits:

- Internal Driver
- Smooth, Consistent Light
- UL for Safety
- No UV, No Mercury
- Long life
- High CRI
- Instant on, no delay or warm up time
- Convenient and quick installation
- Utilizes non- shunted(rapid start) sockets
- Compatible with controls and sensors
- Works in cold temperature applications
- 5 Year Warranty

### Specifications:

| Ordering Code | Replace | Lamp Wattage | Input Voltage | CCT (K) | Initial Lumens | CRI | System Efficacy | Life  |
|---------------|---------|--------------|---------------|---------|----------------|-----|-----------------|-------|
| LT40W/830-ID  | FT40W   | 18           | 120-277       | 3000    | 2160           | 83  | 120             | 50000 |
| LT40W/835-ID  | FT40W   | 18           | 120-277       | 3500    | 2160           | 83  | 120             | 50000 |
| LT40W/840-ID  | FT40W   | 18           | 120-277       | 4000    | 2160           | 83  | 120             | 50000 |
| LT40W/850-ID  | FT40W   | 18           | 120-277       | 5000    | 2160           | 83  | 120             | 50000 |

### Wiring Diagram:



**DLC Listing:**

| Ordering Code | DLC Product ID | DLC Product Model | DLC Version |
|---------------|----------------|-------------------|-------------|
| LT40W/830-ID  | PLH2YZ77E7S7   | LT40W/830-ID      | 5           |
| LT40W/835-ID  | PL9RO5F4B762   | LT40W/835-ID      | 5           |
| LT40W/840-ID  | PLQDM97CJWAI   | LT40W/840-ID      | 5           |
| LT40W/850-ID  | PLORYM7UD48A   | LT40W/850-ID      | 5           |

Specification data is based on tests performed in a controlled environment and represents relative performance. Actual performance can vary depending on operating conditions. Application and performance data subject to change without notice. All specifications are nominal unless noted otherwise.