

Date:	Project:	Type: 3B	Notes:	Catalog #:
-------	----------	--------------------	--------	------------

DL-AOK SERIES LED Commercial Downlight

The DL series is a high-performance field adjustable downlight optimized for new construction and retrofit applications. Change both lumen output and color temperature with the flick of a switch.



Features & Specifications

Applications

Ideal for use for hospitality, retail, office and other commercial lighting applications.

Construction

Die-cast aluminum flange finished and smooth trim with a post-production baked white powder coat. Plastic driver housing and frosted plastic lens.

Mounting

Recessed. Spring loaded retention clips.

Electrical

Utilizes high-efficiency LED power supply and circuit boards. 120/277VAC standard. Multi-color switch (30K, 35K, 40K & 50K). 50/60HZ, 0-10V dimming. <20% THD.

Beam Angle

90° beam angle

Operating Temperature

Suitable for -20°C – 40°C Ambient

Lumen Maintenance

L70 rating of 50,000 hours

Warranty

Five-year warranty. Terms and Conditions Apply. See warranty documentation for more information.

Certification

ETL listed. IP Wet Rated. Adheres to LM79, LM80 and TM21 industry standards. Energy Star Compliant. California JA8 Title 24 Compliant. FCC certified. RoHS compliant.

Performance Data

FSC Part #	Form Factor	Rated Wattage	Delivered Lumens	Efficacy	CRI
DL-6-AOK	6"	7	574	82	>90
		9	738	82	>90
		11	902	82	>90
DL-8-AOK	8"	12	1092	91	>90
		16	1456	91	>90
		22	2002	91	>90
DL-10-AOK	10"	32	3000	93	>90
		37	3500	94	>90
		43	4000	93	>90



DL							
1	2	3					



1 - Series	2 - Diameter in Inches	3 - Type
DL	6 (7 Watt - 574 lumens) (9 Watt - 738 lumens) (11 Watt - 902 lumens) 8 (12 Watt - 1092 lumens) (16 Watt - 1456 lumens) (22 Watt - 2002 lumens) 10 (32 Watt - 3000 lumens) (37 Watt - 3500 lumens) (43 Watt - 4000 lumens)	AOK (Adjustable Output and Kelvin Temp 30K, 35K, 40K & 50K)

Physical Characteristics



Dimensions

Version	Depth	Cut -Out Dimension	Lens Diameter	Outer Edge	Weight
6"	4"	6"	4 1/4"	7 3/8"	.89lbs
8"	4 3/8"	8 1/16"	5 1/4"	9 7/16"	1.12lbs
10"	4 5/8"	10 1/8"	6 1/4"	11 13/16"	1.40lbs

6" Downlight



8" Downlight



10" Downlight

