

Date:	Project:	Type: <b>3B</b>	Notes:	Catalog #:
-------	----------	--------------------	--------	------------

## DL-AOK SERIES LED Commercial Downlight

The DL series is a high-performance field adjustable downlight optimized for new construction and retrofit applications. Change both lumen output and color temperature with the flick of a switch.



### Features & Specifications

#### Applications

Ideal for use for hospitality, retail, office and other commercial lighting applications.

#### Construction

Die-cast aluminum flange finished and smooth trim with a post-production baked white powder coat. Plastic driver housing and frosted plastic lens.

#### Mounting

Recessed. Spring loaded retention clips.

#### Electrical

Utilizes high-efficiency LED power supply and circuit boards. 120/277VAC standard. Multi-color switch (30K, 35K, 40K & 50K). 50/60HZ, 0-10V dimming. <20% THD.

#### Beam Angle

90° beam angle

#### Operating Temperature

Suitable for -20°C – 40°C Ambient

#### Lumen Maintenance

L70 rating of 50,000 hours

#### Warranty

Five-year warranty. Terms and Conditions Apply. See warranty documentation for more information.

#### Certification

ETL listed. IP Wet Rated. Adheres to LM79, LM80 and TM21 industry standards. Energy Star Compliant. California JA8 Title 24 Compliant. FCC certified. RoHS compliant.

### Performance Data

FSC Part #	Form Factor	Rated Wattage	Delivered Lumens	Efficacy	CRI
DL-6-AOK	6"	7	574	82	>90
		9	738	82	>90
		11	902	82	>90
DL-8-AOK	8"	12	1092	91	>90
		16	1456	91	>90
		22	2002	91	>90
DL-10-AOK	10"	32	3000	93	>90
		37	3500	94	>90
		43	4000	93	>90



<b>DL</b>							
1	2	3					


1 - Series	2 - Diameter in Inches	3 - Type
<b>DL</b>	<b>6</b> (7 Watt - 574 lumens) (9 Watt - 738 lumens) (11 Watt - 902 lumens)  <b>8</b> (12 Watt - 1092 lumens) (16 Watt - 1456 lumens) (22 Watt - 2002 lumens)  <b>10</b> (32 Watt - 3000 lumens) (37 Watt - 3500 lumens) (43 Watt - 4000 lumens)	<b>AOK</b> (Adjustable Output and Kelvin Temp 30K, 35K, 40K & 50K)

Physical Characteristics


Dimensions

Version	Depth	Cut -Out Dimension	Lens Diameter	Outer Edge	Weight
6"	4"	6"	4 1/4"	7 3/8"	.89lbs
8"	4 3/8"	8 1/16"	5 1/4"	9 7/16"	1.12lbs
10"	4 5/8"	10 1/8"	6 1/4"	11 13/16"	1.40lbs

6" Downlight



8" Downlight



10" Downlight

